



11 GA. PERFORATED STEEL PANEL ON A 3/4" x 1 1/2" WELDED TUBULAR FRAME.

PANEL AND BOARD ARE POWDER COATED WHITE.



Gared Holdings, LLC
9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

PERFORATED STEEL BOARD 42" X 60"

DRAWN CROSBY DATE 7/26/2019 DATE ISSUED

APPROVED DATE

FILE LOC. Q:\Inventor Files\Specification Files\07_Backboards

SIZE A	SCALE	SHT. NO. 1 OF 2	PART NO. 1260PS	REV B
------------------	-------	--------------------	---------------------------	-----------------

B	WDC	07-26-19
REV	BY	DATE



MODEL 1260PS

60" X 42" RECTANGULAR PERFORATED STEEL BACKBOARD

Backboard shall be constructed of a unitized welded tubular frame utilizing heavy wall rectangular steel tubing. Frame shall include two vertical struts on 35 inch centers with holes for mounting to support structure. Design shall provide a reinforced goal mounting area to allow for direct mounting of goal, board, and structure. Direct mounting design shall have integral holes to allow permanent attachment of board to post and allow for goal replacement without removing the board.

Backboard shall be designed for use with gooseneck and straight arm posts.

Backboard shell shall be constructed of 11 gauge steel with 1/4" diameter holes on 1/2" hole centers to allow a minimum of 24% open area for increased airflow in windy conditions.

Board frame and panel shall be powder coated separately with a white weather resistant finish before being assembled.

GOALS

See Goal-Board Matrix specification sheet for goal compatibility.

Subject to design change and current manufacturing practices.