



B	WDC	05-11-20
REV	BY	DATE




Gared Holdings, LLC
9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

TETHERBALL SYSTEM, 2 3/8" INGROUND

DRAWN	CROSBY	DATE	5/11/2020	DATE ISSUED
APPROVED		DATE		

FILE LOC. Q:\Inventor Files\Specification Files\06_Outdoor Products

SIZE	SCALE	SHT. NO.	PART NO.	REV
A		1 OF 2	6809	B



MODEL 6809
TETHERBALL SYSTEM, 2-3/8" INGROUND

RECOMMENDED APPLICATION

Designed for a permanent tetherball system installed in a concrete footing.

SPECIFICATIONS

The Tetherball post shall be constructed of 2 3/8" O.D. x 13 gauge wall galvanized steel tubing. Base of post shall have a threaded rod installed to insure post does not spin when installed in a concrete footing. The post shall be a total of 12 feet long with 2 feet embedded in the concrete footing. Concrete foundation by others.

System includes post, plated hardware, and tetherball with 9'-10" nylon rope.

WARRANTY

One year from date of purchase. Warranted against manufacturing defects only. Warranty covers damage or failure from normal and intended use of the product, but not abusive activities.

ACCESSORIES

6824 Tetherball Ground Sleeve, 2 3/8" dia.

6825 Sleeve Cap, 2 3/8"

6827 Locking Sleeve Cover, 2 3/8" dia.

Subject to design change and current manufacturing practices.
©2008 Gared Holdings, LLC