

REVISION	
REV.	DATE
A	06/11/09
B	03/03/21
BY	
RWP	
MJP	



Gared Holdings, LLC


 9200 E. 146th St.

 Noblesville, IN 46060



SCHOLASTIC VOLLEYBALL SYSTEM - 2 COURT			
DRAWN	RWP	DATE	06/16/08
APPROVED	CONNORLEY	DATE	06/18/08
FILE LOC.	Q:\Final Release\Specifications		
SIZE	SCALE	SHT. NO.	PART NO.
A	NONE	1 OF 1	
			DWG. NO. 6102
REV	B		

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.





MODEL 6102

TWO COURT SCHOLASTIC TELESCOPING VOLLEYBALL SYSTEM

RECOMMENDED APPLICATION

Top quality unit for use in facilities requiring product for multi-use functions. Meets all grade school, middle school, YMCA, club, USVBA, NFHS, and NCAA requirements for competitive play.

FLOOR SLEEVES AND COVER PLATES

Please refer to attached specification

UPRIGHTS

System shall be supplied with one winch post, one center winch post, and one end post. Upright bottom post shall be lightweight high strength 3 1/2" O.D. aluminum. The upper telescoping adjustable tube shall be 2 7/8" lightweight high strength aluminum. Finish shall be gray anodize. Uprights shall be removable type designed for use with below floor sleeves or above floor T-bases. Uprights shall be provided with adjustable high impact rubber foot to protect finished floors and to allow for additional precise net height adjustment. The uprights will have infinite net height adjustment between 6' to 8'-4" to meet all age group height settings for both men and women.

NET TENSIONER (WINCH)

The net cable tensioner shall incorporate a heavy duty, self-locking worm gear mechanism. A high tensile nylon strap will be used with the winch to achieve required net tension.

NET

Net features include 1" diameter wood dowel and 4" square black nylon mesh (250-lbs tensile strength) for excellent performance and durability. Free floating net along 5/32" diameter steel 7 x 19 cable (2,000-lbs. Minimum breaking strength) allows for quick and easy centering of net about the court lines. Nylon straps with metallic clips are used to secure net in place. Net shall be 32' length and 39" width. Net perimeter shall have a 2" wide vinyl coated polyester hem that is double stitched. Net meets or exceeds all requirements for most levels of competition.

UPRIGHT PADS

Upright safety pads shall be one single piece 72" in height. Padding shall be constructed with 1 1/2" thick cross-linked polyethylene closed cell foam covered with 14-ounce nylon reinforced vinyl. Attachment to uprights shall be with Velcro® straps. Standard Colors are: white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, gray, black, maroon, beige, and purple.

NET ANTENNA AND TAPE

Net antenna shall be 3/8" diameter fiberglass rods 72" long with alternating red and white bands. Net tape shall be white nylon reinforced vinyl 2 1/2" wide with full-length pocket to accept the antenna. Attachment to net shall be full-length quick action Velcro® closures.

AVAILABLE OPTIONS

Referee Stand with optional padding
Storage Cart

Subject to design change and current manufacturing practices.
Revised April 4, 2008 ©2008 Gared Holdings, LLC