



**NOTES:**

1. Designed to develop fitness, strength and coordination
2. (7) rung ladder measures 22" [559 mm] wide x 60" [1524 mm] long.
3. Wall mounted, welded 1-5/16" [33.3 mm] O.D. tubular steel frame with textured black powder coat finish. Rungs are 1" [25.4 mm] O.D. tubing.
4. Heavy duty mounting plates. Wall anchors specified and supplied by others.
5. Suggested mounting height is a minimum of 6'-6" [1.98 m] from lower rung to finished floor.

|     |     |          |
|-----|-----|----------|
| C   | WDC | 06-09-20 |
| REV | BY  | DATE     |



Gared Holdings, LLC  
9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

**GYM LADDER , VERTICAL WALL MOUNT**

|  |        |          |          |             |
|--|--------|----------|----------|-------------|
| DRAWN  | CROSBY | DATE     | 6/9/2020 | DATE ISSUED |
| APPROVED   |        | DATE     |          |             |
| FILE LOC. Q:\Inventor Files\Specification Files\13_Gym Equipment |        |          |          |             |
| SIZE   | SCALE  | SHT. NO. | PART NO. | REV         |
| A  |        | 1 OF 1   | 108      | C           |