



THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

**REBOUND RING, 10"**

|          |        |      |           |             |
|----------|--------|------|-----------|-------------|
| DRAWN    | CROSBY | DATE | 5/28/2020 | DATE ISSUED |
| APPROVED |        | DATE |           |             |

FILE LOC. Q:\Inventor Files\Specification Files\13\_Gym Equipment

|      |       |          |          |     |
|------|-------|----------|----------|-----|
| SIZE | SCALE | SHT. NO. | PART NO. | REV |
| A    |       | 1 OF 2   | RB       | A   |

|     |     |          |
|-----|-----|----------|
| A   | WDC | 05-28-20 |
| REV | BY  | DATE     |



Gared Holdings, LLC  
9200 E. 146th St. Noblesville, IN 46060



**MODEL RB**  
**REBOUND RING**

**APPLICATION**

Rebound ring is ideal for developing rebounding skills. The ring keeps the ball from falling through the basketball goal and only allows a perfect shot to fall through. Rebound ring reduces the goal from standard 18" [457 mm] diameter to 10" [254 mm].

**SPECIFICATION**

The rebound ring shall be constructed of a ½" [12.7 mm] diameter steel rod formed into a ring of 10" [254 mm] inside diameter. Ring shall have 3 mounting points constructed from steel to fit over a standard goal ring. Each mounting point shall be secured to the standard goal with screws. Rebound ring shall be powder coated orange.

Subject to design change and current manufacturing practices.  
Revised March 17, 2009 ©2008 Gared Holdings, LLC