



REVISION		
REV.	DATE	BY
-	-	-



Gared Holdings, LLC
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

WALL PADDING - I BEAM

DRAWN	CONNERLEY	DATE	04/23/13	MATERIAL	N/A
APPROVED	CONNERLEY	DATE	04/23/13	FINISH	N/A
FILE LOC. Q:\Final Release\Specifications				DWG. NO.	4210
SIZE	SCALE	SHT. NO.	PART NO.	REV	
A	NOTED	1 OF 1	4210	-	



MODELS 4206, 4208, 4210, & 4212

I-BEAM PADDING

I-beam pad standard size shall be 6' [1.8 m] x (I-Beam flange width) with a return of 1" [25.4 mm] on each side. Pads to have unpadded vinyl flaps, with 2" loop fastener that wraps around the I-beam. Performance Sports Systems shall supply the hook fastener with adhesive for attachment to the I-beam. Custom size I-beam pads are available. Pads shall be constructed using 2" [50.8 mm] thick 3.5-lbs. density polyurethane foam cemented to 7/16" [11.11 mm] oriented strand board.

Cover material shall be 14-ounce polyester laminated vinyl stapled to backing every two inches. Vinyl to be flame retardant material, which meets NFPA 701, ASTM E84, and CSFM (California State Fire Marshall). Flame retardant vonar® interliner and fire retardant treated plywood backing are also available. Vinyl shall be available in white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, gray, black, maroon, beige, teal and purple.

See model number code chart for specific model number. Custom padding (thickness, material, and color) and size of padding (height and width) must have written description.

Custom cutting and fitting of padding may be done in field to insure proper fit. Furring strips by others.

Model Number Code Chart	
4206	Fits I-Beams with 6" wide flanges
4208	Fits I-Beams with 8" wide flanges
4210	Fits I-Beams with 10" wide flanges
4212	Fits I-Beams with 12" wide flanges