



MODEL 4510 COLUMN PADDING

REVISION		
REV.	DATE	BY
-	-	-

Gared Holdings, LLC
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

WALL PADDING - COLUMN					
DRAWN	CONNERLEY	DATE	04/18/13	MATERIAL	N/A
APPROVED	CONNERLEY	DATE	04/18/13	FINISH	N/A
FILE LOC. Q:\Final Release\Specifications				DWG. NO.	4510
SIZE	SCALE	SHT. NO.	PART NO.	REV	
A	NOTED	1 OF 1	4510	-	



MODEL 4510

COLUMN PADDING

Column padding shall be constructed as a wood backed u-shaped pad with 1" [25.4 mm] nailing lip on top and bottom of each panel for square columns or a wrap-around pad for round columns, using hook and loop fastener straps for attachment to the column. Size must be specified. Pads shall be constructed using 2" [50.8 mm] thick 3.5-lbs. density polyurethane foam cemented to 7/16" [11.11 mm] oriented strand board.

Cover material shall be 14-ounce polyester laminated vinyl stapled to backing every two inches. Vinyl to be flame retardant material, which meets NFPA 701, ASTM E84, and CSFM (California State Fire Marshall). Vinyl shall be available in white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, gray, black, maroon, beige, teal and purple.

Custom cutting and fitting of padding may be done in field to insure proper fit. Furring strips by others.

ACCESSORIES

WALL ATTACHMENT TRIMS AND HARDWARE

Most wall padding may be attached with special attachment trims and hardware. See the wall padding section in the specification manual.