



MATERIAL:
 PAD - 1.50" THICK CROSS-LINKED CELL POLYETHYLENE FOAM.
 COVERING - 14 OUNCE NYLON REINFORCED VINYL.

REVISION		
REV.	DATE	BY

PSS
 PERFORMANCE
 SPORTS SYSTEMS

GAREDTM

Gared Holdings, LLC
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

UPRIGHT POST PAD

DRAWN DKH	DATE 10/20/09	MATERIAL N/A
APPROVED JJC	DATE 10/20/09	FINISH N/A
FILE LOC. Q:\Final Release\Specifications	DWG. NO. 6010	
SIZE A	SCALE NONE	SHT. NO. 1 OF 1
		PART NO. 6010
		REV



MODEL 6010
UPRIGHT POST PAD

Upright safety pad for end posts shall be one piece, 72" in height. Padding shall be constructed with minimum 1 1/2" thick cross-linked polyethylene closed cell foam, covered with 14-ounce, nylon-reinforced vinyl. Attachment to upright shall be effected by Velcro® straps. Colors available are white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, dark blue, gray, black, maroon, beige, teal and purple.

See model number code chart for volleyball padding for specific model number.

Custom colors must have a written description.