



REVISION		
REV.	DATE	BY
A	08/12/09	RWP



**PSS**  
PERFORMANCE  
SPORTS SYSTEMS



**G**  
GARED™

**Gared Holdings, LLC**  
9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

**3-1/2" ABOVE FLOOR END BASE SLEEVE**

DRAWN	RWP	DATE	08/12/09	MATERIAL	N/A
APPROVED	-	DATE	-	FINISH	N/A
FILE LOC. Q:\Final Release\Specifications				DWG. NO.	6406 T-BASE
SIZE	SCALE	SHT. NO.	PART NO.	<b>6406</b>	
<b>A</b>	NONE	1 OF 1			
					REV <b>A</b>



**MODEL 6406**  
**VOLLEYBALL T-BASE**

**RECOMMENDED APPLICATION**

Designed for use in facilities where a sub-floor structure is not adequate to accommodate the installation of a floor sleeve.

**SPECIFICATIONS**

T-base shall be constructed of welded steel capable of accepting a 3.5" diameter volleyball post. The gross dimensions will be 12" high x 17.75 " long x 18" wide. T-base is securely locked in place with a 1/2" threaded rod with hand knob screwed into a 1/2" diameter, 13 thread per inch, floor anchor (choose anchor from below). Rubber pads protect floor from damage.

Center T-base available for multi-court play (Model 6408) and requires two floor anchors.

**Floor Anchors**

Style B – For wood floors installed directly over concrete

Style BX – For wood floors installed directly over concrete, except knurled anchor has been extended to 3-1/4"

Style C – For concrete floors or synthetic floors installed directly over concrete

Style E – For floating wood floors resting on sleepers or metal clip fasteners

**Optional T-Base Padding**

6050 – T-base pad

6060 – Center T-base pad

Colors available are white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, dark blue, gray, black, maroon, beige, teal and purple.