



**NOTE:**  
 BACKBOARD THICKNESS - 2 1/8".  
 MATERIAL - 1/2" THICK TEMPERED GLASS WITH ALUMINUM FRAME.  
 FINISH - GRAY POWDERCOAT ON BRACKETS AND PLATES.

REVISION		
REV.	DATE	BY
A	12/01/03	JJC
B	06/06/08	RWP



Gared Holdings, LLC  
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

**48" ALUMINUM FRAME GLASS BACKBOARD**

DRAWN	CONNERLEY	DATE	05/02/03	MATERIAL	AS NOTED
APPROVED	JJC	DATE	05/02/03	FINISH	AS NOTED
FILE LOC. Q:\Final Release\Specifications				DWG. NO.	AFRG48
SIZE	SCALE	SHT. NO.	PART NO.	REV	B
A	NOTED	1 OF 1	AFRG48		



## **MODEL AFRG48**

### **ALUMINUM FRAME 72" X 48" RECTANGULAR GLASS BACKBOARD**

The AFRG48 backboard shall be fabricated with an aluminum frame constructed of 0.200' thick extruded "F" channel with steel corner brackets. All steel components shall be powder coated with a durable gray finish. An aluminum-capped frame will not be acceptable. Manufacturer of backboard shall have over ten years experience. Backboard shall meet NCAA and high school requirements.

Glass shall be 1/2" in thickness and fully tempered with white target and border lines permanently fused onto surface. 12mm glass will not be considered equal to 1/2" glass, with a nominal thickness range of .485" to .515", and will not be used as a substitute for full 1/2" glass. Vinyl shock absorbing material shall insulate glass from frame. Goal mounting holes shall be on 5" horizontal and 5" vertical centers. Shock insulating pads shall be used between steel mounting plate and glass to protect against possible breakage.

#### **ACCESSORIES**

#### **GOALS**

Compatible goals are models 1000, 2000+, 2500, 3000, 20123T-A (Snap A), and 5500. See goal section in specification manual.

Subject to design change and current manufacturing practices.  
Revised April 4, 2008 ©2008 Gared Holdings, LLC